ds.tools
DISTRIBUTED SIMULATION TOOLS

coreDS™

Distributed simulation made easy with coreDS™

Overview

coreDS™ is an easy-to-use multi-platform C++ API for rapidly connecting to an HLA federation, a DIS simulation or CIGI host/IG.


Save time and money; as few as five lines of code are needed for a complete integration.

Once integrated, no further recompilation is required – everything is done at runtime through the provided GUIs, including data mapping and distributed simulation configuration.

coreDS™ provides an elegant and cost-effective solution for adding HLA, DIS and CIGI support to your C++ software.

Main features

- Cost-effective solution using proven technologies – save time and money;
- Provides configuration graphical user interfaces you can integrate into your software;
- Switches configuration at runtime – between HLA, DIS and CIGI, to a new set of mappings, to a different FOM, or anything else you can think of;
- Lightweight scripting engine (LUA) for on-the-fly data conversion;
- Data mapping at runtime – change your FOM file or PDU mapping on the fly;
- Automatic data encoding/decoding;
- Integrated dead reckoning;
- No code generation required;
- Integrated data filtering;
- Supports most distributed simulation concepts out of the box.



High-Level Architecture (HLA)

Supported protocols

- HLA – DOD 1.3
- HLA – IEEE 1516-2000
- HLA – IEEE 1516-2010 (HLA1516e)
- HLA – IEEE 1516-2025 (HLA4)

Supported RTIs

- All commercial RTIs (Pitch, MAK, RTI Ng Pro, RTI-S, Raytheon RTI, CAE RTI)
- Most OpenSource RTIs (Portico, CERTI, OpenRTI)

Supported FOMs

- Supports any valid FOM file
- Tested with the RPR FOM and NETN FOM

Distributed Interactive Simulation (DIS)

Supported protocols

- DIS 5 (IEEE 1278.1-1995)
- DIS 6 (IEEE 1278.1a-1998)
- DIS 7 (IEEE 1278.1-2012)
- DIS 8 (IEEE 1278.1-202X)
- C-DIS (SISO-STD-023-2024)

Supported PDUs

- All PDUs are supported
- Custom PDUs are supported

Common Image Generator Interface (CIGI)

Supported protocols

- CIGI 4
- CIGI 3.0 to 3.3